



Rubrik 2.21

Leichte Reihe - 45°-Bogen



Für Gegenschluss mit 24°-Konus und Schneidringverschraubungen DIN 2353 / DIN EN ISO 8434-1 Leichte Reihe = DKOL - 45° O-Ring = NBR
Auf Anfrage: FKM

Schlauch	DN	Gewinde	Rohr A.D.	Ca. Maße				O-Ring	Bestellzeichen
DN	in.	G	D	A	B	C	SW		
05	3/16"	M 12 x 1,5	6	44,5	22,5	3,0	14	4 x 1,5	DKOL-06-45°-DN 05
06	1/4"	M 12 x 1,5	6	37,0	15,0	4,0	14	5 x 1,0	DKOL-06-45°-DN 06
05	3/16"	M 14 x 1,5	8	37,0	16,5	3,0	17	6 x 1,5	DKOL-08-45°-DN 05
06	1/4"	M 14 x 1,5	8	38,5	16,5	4,0	17	6 x 1,5	DKOL-08-45°-DN 06
08	5/16"	M 14 x 1,5	8	51,0	26,0	4,5	17	6 x 1,5	DKOL-08-45°-DN 08
06	1/4"	M 16 x 1,5	10	38,5	16,5	4,0	19	8 x 1,5	DKOL-10-45°-DN 06
08	5/16"	M 16 x 1,5	10	44,5	19,0	5,5	19	8 x 1,5	DKOL-10-45°-DN 08
10	3/8"	M 16 x 1,5	10	45,5	20,0	7,0	19	8 x 1,5	DKOL-10-45°-DN 10
06	1/4"	M 18 x 1,5	12	42,0	19,5	4,0	22	10 x 1,5	DKOL-12-45°-DN 06
08	5/16"	M 18 x 1,5	12	44,5	19,0	5,5	22	10 x 1,5	DKOL-12-45°-DN 08
10	3/8"	M 18 x 1,5	12	43,5	18,5	7,0	22	10 x 1,5	DKOL-12-45°-DN 10
12	1/2"	M 18 x 1,5	12	62,5	27,5	8,5	22	10 x 1,5	DKOL-12-45°-DN 12
10	3/8"	M 22 x 1,5	15	53,5	21,5	7,0	27	12 x 2,0	DKOL-15-45°-DN 10
12	1/2"	M 22 x 1,5	15	54,5	20,5	9,5	27	12 x 2,0	DKOL-15-45°-DN 12
12	1/2"	M 26 x 1,5	18	60,5	23,5	9,0	32	15 x 2,0	DKOL-18-45°-DN 12
16	5/8"	M 26 x 1,5	18	65,0	26,5	12,5	32	15 x 2,0	DKOL-18-45°-DN 16
19	3/4"	M 26 x 1,5	18	76,5	40,0	13,0	32	15 x 2,0	DKOL-18-45°-DN 19
16	5/8"	M 30 x 2	22	67,5	28,0	12,0	36	19 x 2,0	DKOL-22-45°-DN 16
19	3/4"	M 30 x 2	22	70,0	28,0	14,5	36	19 x 2,0	DKOL-22-45°-DN 19
19	3/4"	M 36 x 2	28	79,0	34,0	14,5	41	25 x 2,0	DKOL-28-45°-DN 19

25	1"	M 36 x 2	28	93,0	33,0	20,0	41	25 x 2,0	DKOL-28-45°-DN 25
31	1 1/4"	M 45 x 2	35	100,0	44,0	25,0	50	32 x 2,5	DKOL-35-45°-DN 31
38	1 1/2"	M 45 x 2	35				50	32 x 2,5	DKOL-35-45°-DN 38
31	1 1/4"	M 52 x 2	42	114,5	45,0	25,0	60	38 x 2,5	DKOL-42-45°-DN 31
38	1 1/2"	M 52 x 2	42	111,0	48,0	31,0	60	38 x 2,5	DKOL-42-45°-DN 38