


Rubrik 6.25

EVW-Verschraubungen - 90° - Whitworth



Einstellbare Winkel-Verschraubungen - 90° Einschraubgewinde G: Whitworth-Rohrgewinde - Zylindrisch
 Abdichtung durch gekammerten O-Ring (FKM) - ISO 1179

Druck	Rohr A.D.		Gewinde		Ca. Maße				O-Ring	Bestellzeichen	Brutto- Preis (€)
	PN	mm	in.	G1 = UNF/UN	G = BSP	L	L1	SW1			
250	6	1/4"	7/16"-20	1/8"	22,6	26,5	14	11	8 x 2,2	1252530-04-02	28,20
200	6	1/4"	7/16"-20	1/4"	22,6	32,0	19	14	10,77 x 2,62	1252530-04-04	28,20
200	8	5/16"	1/2"-20	1/4"	26,6	32,0	19	14	10,77 x 2,62	1252530-05-04	28,20
200	10	3/8"	9/16"-18	1/4"	26,9	32,0	19	14	10,77 x 2,62	1252530-06-04	28,50
200	10	3/8"	9/16"-18	3/8"	29,0	37,0	22	19	13,94 x 2,62	1252530-06-06	37,50
200	10	3/8"	9/16"-18	1/2"	31,0	43,0	27	22	17,86 x 2,62	1252530-06-08	44,60
200	12	1/2"	3/4"-16	3/8"	31,8	37,0	22	19	13,94 x 2,62	1252530-08-06	40,60
200	12	1/2"	3/4"-16	1/2"	33,8	43,0	27	22	17,86 x 2,62	1252530-08-08	44,55
200	14, 15, 16	5/8"	7/8"-14	1/2"	36,8	43,0	27	22	17,86 x 2,62	1252530-10-08	44,55
200	18, 20	3/4"	1 1/16"-12	1/2"	42,2	49,5	27	27	17,86 x 2,62	1252530-12-08	60,90
200	18, 20	3/4"	1 1/16"-12	3/4"	42,2	49,5	36	27	23,47 x 2,62	1252530-12-12	61,50
200	25	1"	1 5/16"-12	1"	46,0	52,0	41	33	29,74 x 3,53	1252530-16-16	89,90
160	28, 30, 32	1 1/4"	1 5/8"-12	1 1/4"	52,3	57,0	50	41	37,69 x 3,53	1252530-20-20	157,50
140	35, 38	1 1/2"	1 7/8"-12	1 1/2"	59,2	61,0	55	50	44,04 x 3,53	1252530-24-24	285,50